

ANTARTIC-SIL/12 SIR



Ficha Técnica *Technical Sheet* *Fiche technique*

Manguera antiabrasiva de mandrino para impulsión de hielo seco en procesos de limpiezas abrasivas por criogenia donde se tiene que evitar la formación de polvo.

Tuyau anti-abrasif fabriqué sur manchette pour le refoulement de glace sèche dans des opérations de propreté cryogène et où il faut éviter la formation de poudre.

Mandrel built hose for blasting operations with dry ice which limits the formation of dust.



Características técnicas *Technical Characteristics* *Caractéristiques techniques*

Interior	Silicona roja.	Intérieur	Silicone rouge	Tube	Red silicon
Refuerzo	Textil de alta tenacidad y trenza para la descarga electrostática	Renfort	Textile de haute ténacité et tresse de cuivre pour la décharge électrostatique	Reinforcement	High tensile textile plies and antistatic copper wire.
Exterior	Silicona roja, resistente a la parafina, a la abrasión y a la intemperie.	Extérieur	Silicone rouge, résistant à la paraffine, à l'abrasion et aux intempéries.	Cover	Red silicon abrasion, paraffin oil and weather resistant.
Temperatura	-85°C +200°C	Température	-85°C +200°C	Temperature	-85°C +200°C

Marcado / Marquage/ Marking  THOR ANTARTIC DRY ICE BLASTING (in white letters)

Medidas *Sizes* *Mesures*

Ref.	I.D. mm	O.D. mm	Appr. Weight kg/m	Working Pressure Bar	Burst pressure Bar	Vacuum bar	Bending Radius mm	Stock
ANTARS.016	16	27	0.40	12	36			
ANTARS.019	19	30	0.45	12	36			
ANTARS.022	22	32	0.50	12	36			
ANTARS.025	25	35	0.55	12	36			
ANTARS.028	28	38	0.60	12	36			