

ARMORVINPRESS PU

Manguera de PVC con espiral de acero galvanizado de paso reducido, capa interna de poliuretano, para aspiración e impulsión de líquidos, aire y aceites en neumática, aceite hidráulico, e industria química.

913038



PVC hose with embedded reduce pitch steel spiral, internal layer in polyurethane, for suction and delivery of liquids, air and oils in pneumatic, hydraulic oil, and chemical industry.

	SUPERFÍCIES LISAS SMOOTH SURFACE	*****
	FLEXIBILIDAD FLEXIBILITY	****
	RESISTENCIA A LA ABRASIÓN ABRASION RESISTANCE	***
	TEMPERATURA DE USO TEMPERATURE RANGE	-20° C + 90° C
	RESISTENCIA QUÍMICA CHEMICAL RESISTANCE	tabla PU
	RESISTENCIA AL APLASTAMIENTO CRUSHING RESISTANCE	***

Conforme a FDA 21 CFR 177.2600 par. "e"/"f" (alimentos acuosos, alimentos grasos).

Produced according to FDA 21 CFR 177.2600 par. "e"/"f" (watery foodstuff, fatty foodstuff).

Ø INTERIOR Ø I.D.	Ø INTERIOR Ø I.D.	Ø EXTERIOR Ø O.D.	PESO WEIGHT	RADIO CURVATURA BENDING RADIUS	PRESIÓN TRABAJO WORKING PRESS.	PRESIÓN ROTURA BURSTING PRESS.	VACÍO VACUUM	LONGITUD ROLLO COIL LENGTH
pulgadas	mm	mm	g/m	mm	bar	bar	m H ₂ O	mt
3/16	5	10	80	20	20	60	9	60
	6	11	95	23	20	60	9	60
1/4	6,4	11,5	100	26	20	60	9	60
5/16	8	13,5	135	32	18	54	9	60
3/8	9,5	15,5	165	38	18	54	9	60
	10	16	180	40	17	51	9	60
	12	18	210	45	16	48	9	60
1/2	12,7	19	230	50	15	45	9	60
	14	20,5	240	56	14	42	9	60
5/8	16	23	290	63	14	42	9	60
	18	25	320	70	12	36	9	60
3/4	19	26	320	76	12	36	9	60
	20	27	340	80	12	36	9	60

