

ARMORVIN® TOTAL PU OIL TPHF

Manguera de PU con espiral de acero galvanizado para aspiración e impulsión de líquidos alimentarios y aceites vegetales.

912873



Soft PVC PHF hose with embedded galvanized steel spiral and PU underlayer, for delivery and suction of food liquids, food oils and food fats.

	SUPERFÍCIES LISAS SMOOTH SURFACE	*****
	FLEXIBILIDAD FLEXIBILITY	**
	RESISTENCIA A LA ABRASIÓN ABRASION RESISTANCE	***
	TEMPERATURA DE USO TEMPERATURE RANGE	-40° C + 90° C
	RESISTENCIA QUÍMICA CHEMICAL RESISTANCE	tabla PU
	RESISTENCIA AL APLASTAMIENTO CRUSHING RESISTANCE	***
	RESISTENCIA AL OZONO OZONE RESISTANCE	*****
	SIN O-FTALATOS O-PHTHALATE FREE	PHF *****
	SIN FTALATOS PHTHALATE FREE	TPHF *****
	IDÓNEO AL CONTACTO CON ALIMENTOS SEGÚN LA DECLARACIÓN DE CONFORMIDAD. SUITABLE FOR CONTACT WITH FOODSTUFF ACCORDING TO THE DECLARATION OF CONFORMITY	

Ø INTERIOR Ø I.D.	Ø INTERIOR Ø I.D.	Ø EXTERIOR Ø O.D.	PESO WEIGHT	RADIO CURVATURA BENDING RADIUS	PRESIÓN TRABAJO WORKING PRESS.	PRESIÓN ROTURA BURSTING PRESS.	VACÍO VACUUM	LONGITUD ROLLO COIL LENGTH
pulgadas	mm	mm	g/m	mm	bar	bar	m H ₂ O	mt
1	20	28,5	410	80	7	21	9	30
	25	33,2	520	100	7	21	9	30
	30	39,2	620	120	7	21	9	30
	40	49,4	900	160	6	18	8	30
	50	60,4	1160	200	6	18	8	30
	60	70	1440	240	6	18	8	30
	70	80	1650	300	5	15	8	30
	75	85	1730	320	5	15	7	30
	80	90	1800	340	4	12	7	30
	100	114	3250	400	3	9	7	20

