

Ficha Técnica *Technical Sheet* *Fiche technique*

Manguera antiabrasiva de mandrino para impulsión de SCC (Self Compacting Concrete). Se utiliza como terminal de las bombas de hormigón.

Tuyau anti-abrasif fabriqué sur manchette pour le refoulement de SCC (Self Compacting Concrete). Il est utilisé comme terminal pour les pompes à béton.

Mandrel built textile reinforced concrete placement hose. Suitable for SCC (Self Compacting Concrete).



Características técnicas *Technical Characteristics* *Caractéristiques techniques*

Interior	Caucho NR negro conductor de alta resistencia.	Intérieur	Caoutchouc NR noir conducteur de haute résistance.	Tube	Black NR conductive rubber, high resistance to abrasion.
Refuerzo	Textil de alta tenacidad.	Renfort	Textile de haute ténacité.	Reinforcement	High tensile textile plies.
Exterior	Caucho negro conductor, resistente a la abrasión, intemperie y ozono	Extérieur	Caoutchouc noir conducteur, résistant à l'abrasion, à l'ozone et aux intempéries.	Cover	Black conductive rubber, resistant to weather and abrasion.
Temperatura	-40°C +80°C	Température	-40°C +80°C	Temperature	-40°C +80°C

Marcado / Marquage/ Marking  Thor DRAGA CONCRETE PUMP HOSE W.P. 85 BAR – S.F. 2,00 – MADE IN ITALY (green).

Medidas *Sizes* *Mesures*

Ref.	I.D. mm	O.D. mm	Appr. Weight kg/m	Working Pressure Bar	Burst pressure Bar	Vacuum bar	Bending Radius mm	Stock
DRA60.038	38	59	1.88	60	180			*
DRA60.051	51	72	2.39	60	180			*
DRA60.065	65	87	3.12	60	180			
DRA60.076	76	100	3.70	60	180			*
DRA60.102	102	130	5.70	60	180			