

Ficha Técnica Technical Sheet Fiche technique

Manguera antiabrasiva de mandrino para impulsión de arenas, granallas abrasivas y gunitado (abrasión seca o húmeda) normalmente empleada para el tratamiento de superficies (chorro de arena) o impulsión de mortero.

Tuyau anti-abrasif fabriqué sur manchette pour le refoulement de sables, corindon, grenailles abrasives (abrasion sèche ou humide) normalement utilisé pour le traitement de surfaces (jets de sable) ou refoulement de mortier.

Mandrel built highly abrasion resistant sand, corundum, shot and grit blast delivery hose, normally used for surface treatment.



Características técnicas Technical Characteristics Caractéristiques techniques

Interior	Caucho NR negro conductor. R<5x10 ⁴ Ω/m.	Intérieur	Caoutchouc NR noir conducteur. R<5x10 ⁴ Ω/m.	Tube	Black NR conductive rubber. R<5x10 ⁴ Ω/m.
Refuerzo	Textil de alta tenacidad.	Renfort	Textile de haute ténacité.	Reinforcement	High tensile textile plies.
Exterior	Caucho NR negro conductor, resistente a la abrasión y a la intemperie.	Extérieur	Caoutchouc NR noir conducteur, résistant à l'abrasion et aux intempéries.	Cover	Black NR rubber, weather and abrasion resistant. Fabric impression.
Temperatura	-40°C +70°C	Température	-40°C +70°C	Temperature	-40°C +70°C

Marcado / Marquage/ Marking  THOR ANTISTATIC SHOTBLAST - WP 20 BAR 300 PSI (in orange letters)

Medidas Sizes Mesures

Ref.	I.D. mm	O.D. mm	Appr. Weight kg/m	Working Pressure Bar	Burst pressure Bar	Vacuum bar	Bending Radius mm	Stock
DUN20.025	25	40	0.95	20	60			
DUN20.038	38	54	1.70	20	60			
DUN20.050	50	70	2.50	20	60			
DUN20.060	60	80	3.10	20	60			
DUN12.065	65	85	3.60	20	60			