

OREGON PU ET

Manguera de Poliuretano (PU) Poliéter con espiral de PVC rígido antigolpes, para aspiración y transporte de materiales abrasivos y alimentos secos.



SUPERFÍCIES LISAS

SMOOTH SURFACE



FLEXIBILIDAD

FLEXIBILITY



RESISTENCIA A LA ABRASIÓN

ABRASION RESISTANCE



TEMPERATURA DE USO

TEMPERATURE RANGE

-25° C + 85° C



RESISTENCIA QUÍMICA

CHEMICAL RESISTANCE

tabla PU



RESISTENCIA AL APLASTAMIENTO

CRUSHING RESISTANCE



RESISTENCIA AL OZONO

OZONE RESISTANCE



RESISTENCIA A LOS MICROORGANISMOS

MICROORGANISMS RESISTANCE



HIDRÓLISIS

HYDROLYSIS

Resistente a la hidrólisis en agua caliente a 60°C.
Resistant to hydrolysis in 60° C warm water.



IDÓNEO AL CONTACTO CON ALIMENTOS SEGÚN LA DECLARACIÓN DE CONFORMIDAD.

SUITABLE FOR CONTACT WITH FOODSTUFF ACCORDING TO THE DECLARATION OF CONFORMITY

911003



Polyurethane polyether hose with shockproof PVC spiral, for suction and transport of abrasive materials and dry foods.

Ø INTERIOR Ø I.D.	Ø INTERIOR Ø I.D.	Ø EXTERIOR Ø O.D.	ESPESOR PARED WALL THICKNESS	PESO WEIGHT	RADIO CURVATURA BENDING RADIUS	PRESIÓN TRABAJO WORKING PRESS.	PRESIÓN ROTURA BURSTING PRESS.	VACÍO VACUUM	LONGITUD ROLLO COIL LENGTH
pulgadas	mm	mm	mm	g/m	mm	bar	bar	m H ₂ O	mt
1	25	30,8	0,6	160	25	0,6	1,8	4	20
	30	35,8	0,6	190	30	0,6	1,8	4	20
1 1/4	32	38	0,6	195	32	0,6	1,8	4	20
	35	41	0,6	210	35	0,4	1,2	4	20
1 1/2	38	44,4	0,6	250	38	0,4	1,2	3	20
	40	46	0,6	280	40	0,4	1,2	3	20
1 3/4	45	51,6	0,6	320	45	0,4	1,2	3	20
	50	57,4	0,7	390	50	0,4	1,2	3	20
	60	68	0,7	440	60	0,4	1,2	3	20
2 1/2	63	71,5	0,7	470	63	0,3	0,9	3	20
	70	78,4	0,7	600	70	0,3	0,9	3	20
	75	83,4	0,7	600	75	0,3	0,9	3	20
	80	89	0,7	650	80	0,2	0,6	3	20
	90	99,6	0,8	750	90	0,2	0,6	3	20
	100	109,6	0,8	850	100	0,2	0,6	3	20
	110	121	0,8	1050	110	0,2	0,6	3	20
	120	131,5	0,8	1100	120	0,15	0,45	3	20
	125	136,5	0,8	1170	125	0,15	0,45	3	20
	130	142	0,8	1280	130	0,15	0,45	3	20
	140	152	0,9	1400	140	0,1	0,3	3	20
	150	162	0,9	1500	150	0,1	0,3	3	20
	160	172,4	0,9	1700	160	0,1	0,3	3	20
	180	193	0,9	2000	180	0,1	0,3	3	10
	200	214	0,9	2180	200	0,1	0,3	3	10
	250	265	1	2960	250	0,1	0,3	3	10
	300	320	1	3700	300	0,1	0,3	3	10

