

TERMOFLEX 300°C DOBLE CAPA

Manguera de doble capa de tejido de fibra de vidrio recubierto de silicona con espiral de acero galvanizado, para aspiración de humos y aire caliente.

912995



Hose made in silicone coated fiberglass with galvanised steel spiral embedded between two layers of silicone, for suction of fumes and hot air.

	SUPERFÍCIES LISAS SMOOTH SURFACE	*****
	FLEXIBILIDAD FLEXIBILITY	*****
	RESISTENCIA A LA ABRASIÓN ABRASION RESISTANCE	*****
	TEMPERATURA DE USO TEMPERATURE RANGE	-85° C + 300°C
	RESISTENCIA QUÍMICA CHEMICAL RESISTANCE	SILICONA
	RESISTENCIA AL APLASTAMIENTO CRUSHING RESISTANCE	***

Ø INTERIOR Ø I.D.	Ø INTERIOR Ø I.D.	Ø EXTERIOR Ø O.D.	PESO WEIGHT	RADIO CURVATURA BENDING RADIUS	PRESIÓN TRABAJO WORKING PRESS.	PRESIÓN ROTURA BURSTING PRESS.	VACÍO VACUUM	LONGITUD ROLLO COIL LENGTH
pulgadas	mm	mm	g/m	mm	bar	bar	m H ₂ O	mt
2	51	56	331	51	2,5	7,5	5	4
2 1/2	63	68	415	63	2,4	7,2	4,5	4
	70	75	500	70	2,3	6,9	4,5	4
3	76	81	531	76	2,3	6,9	4	4
	83	87	590	83	2,1	6,3	4	4
3 1/2	89	94	610	89	2,1	6,3	3,95	4
4	102	107	710	102	1,9	5,7	3,05	4
	114	120	845	114	1,6	4,8	2,8	4
	121	127	980	121	1,5	4,5	2,7	4
5	127	133	925	127	1,4	4,2	2,2	4
	140	146	1020	140	1,8	5,4	1,8	4
6	152	158	1200	152	1,7	5,1	1,7	4
	178	189	1430	178	1,2	3,6	1,2	4
8	203	209	1650	203	0,9	2,7	0,9	4
10	254	260	1140	254	0,4	1,2	0,4	4
12	305	311	1580	305	0,2	0,6	0,3	4



Tejido de fibra de vidrio
recubierto de Silicona

Silicone coated fiberglass

Espiral en acero galvanizado
Galvanised steel spiral

