

VACUPRESS ENO PHF

Manguera de PVC plastificado de doble capa sin o-ftalatos con espiral de acero galvanizado reforzada con fibra de poliéster, para aspiración e impulsión de líquidos, vino y bebidas con hasta el 20% de contenido alcohólico.

	SUPERFÍCIES LISAS SMOOTH SURFACE	*****
	FLEXIBILIDAD FLEXIBILITY	*****
	RESISTENCIA A LA ABRASIÓN ABRASION RESISTANCE	***
	TEMPERATURA DE USO TEMPERATURE RANGE	-25°C +60°C
	RESISTENCIA QUÍMICA CHEMICAL RESISTANCE	tabla PVC
	RESISTENCIA AL APLASTAMIENTO CRUSHING RESISTANCE	***
	SIN O-FTALATOS O-PHTHALATE FREE	PHF *****
	ADECUADO PARA APLICACIONES EN CONTACTO CON ALIMENTOS DE ACUERDO CON LAS REGULACIONES UE - VER DECLARACIÓN DE CONFORMIDAD SUITABLE FOR FOOD CONTACT APPLICATIONS ACCORDING TO EU REGULATION - SEE DECLARATION OF CONFORMITY	

913843



o-Phthalate free plasticized PVC double layer hose with steel spiral and polyester yarn reinforcement, for suction and delivery of liquids, wine and beverages with up to 20% alcoholic content.

Ø NOMINAL Ø NOMINAL	Ø NOMINAL Ø NOMINAL	Ø INTERIOR Ø I.D.	Ø EXTERIOR Ø O.D.	PESO WEIGHT	RADIO CURVATURA BENDING RADIUS	PRESIÓN TRABAJO WORKING PRESS.	PRESIÓN ROTURA BURSTING PRESS.	VACÍO VACUUM	LONGITUD ROLLO COIL LENGTH
inch	mm	mm	mm	g/m	mm	bar	bar	m H ₂ O	m
3/4	19	19	28	475	70	20	60	9	60
1	25	25	35,5	680	80	16	48	9	60
	30	30	40,5	770	90	16	48	9	60
1 1/4	32	32	42,5	800	100	16	48	9	60
	35	35	47	1100	115	14	42	9	60
1 1/2	38	38	51	1200	125	14	42	9	30
	40	40	53	1220	130	14	42	9	30
1 3/4	45	45	58	1400	140	12	36	9	30
2	50	50	64	1600	150	12	36	9	30
	60	60	74	2000	180	12	36	9	30
2 1/2	63	63	77	2100	190	12	36	9	30
	70	70	85,5	2700	190	12	36	9	30
	75	75	91	2850	190	12	36	9	30
3	76	76	92	2900	210	12	36	9	30
	80	80	96	2950	220	10	30	9	30
3 1/2	90	90	107	3500	250	10	30	9	30
	100	100	117	3950	295	10	30	9	30
4	102	102	119	4000	300	10	30	9	30
	120	120	138	5300	350	8	24	9	20
5	127	127	145	5800	370	7	21	9	20
	150	150	169	6800	480	5	15	9	20
6	152	152	171	6850	480	5	15	9	20
	200	200	222	10300	650	3	9	9	12
8	203	203	225	10500	650	3	9	9	12

