

VACUPRESS FOOD

Manguera termoplástica multicapa reforzada con espiral de acero y fibras de poliéster, para aspiración e impulsión de líquidos, así como alimentos líquidos incluidos productos lácteos.

	SUPERFÍCIES LISAS SMOOTH SURFACE	*****
	FLEXIBILIDAD FLEXIBILITY	****
	RESISTENCIA A LA ABRASIÓN ABRASION RESISTANCE	**
	TEMPERATURA DE USO TEMPERATURE RANGE	-25°C +80°C
	RESISTENCIA QUÍMICA CHEMICAL RESISTANCE	tabla TPV
	RESISTENCIA AL APLASTAMIENTO CRUSHING RESISTANCE	***

FDA ADECUADO PARA APLICACIONES EN CONTACTO CON ALIMENTOS DE ACUERDO CON LAS REGULACIONES FDA - VER DECLARACIÓN DE CONFORMIDAD
SUITABLE FOR FOOD CONTACT APPLICATIONS ACCORDING TO FDA REGULATION - SEE DECLARATION OF CONFORMITY

913908



Multilayer thermoplastic hose reinforced with steel spiral and polyester yarns, for suction and delivery of liquids also liquid foodstuffs. Suitable for food contact applications, only according to FDA regulations.

Ø NOMINAL Ø NOMINAL	Ø NOMINAL Ø NOMINAL	Ø INTERIOR Ø I.D.	Ø EXTERIOR Ø O.D.	PESO WEIGHT	RADIO CURVATURA BENDING RADIUS	PRESIÓN TRABAJO WORKING PRESS.	PRESIÓN ROTURA BURSTING PRESS.	VACÍO VACUUM	LONGITUD ROLLO COIL LENGTH
inch	mm	mm	mm	g/m	mm	bar	bar	m H ₂ O	m
3/4	19	19	28	380	70	-	-	9	60
	22	22	31,5	450	75	-	-	9	60
1	25	25	35,5	580	80	14	42	9	60
	30	30	40,5	650	85	-	-	9	60
1 1/4	32	32	42,5	730	90	10	30	9	60
	35	35	47	900	95	-	-	9	60
1 1/2	38	38	50	920	100	10	30	9	30
	40	40	52	970	110	10	30	9	30
	42	42	54	1030	115	-	-	9	30
1 3/4	45	45	57	1100	120	-	-	9	30
2	50	50	62,5	1280	130	10	30	9	30
	53	53	66	1350	140	-	-	9	30
	54	54	67	1350	150	-	-	9	30
	60	60	73	1550	160	-	-	9	30
2 1/2	63	63	76	1600	180	-	-	9	30
3	76	76	91	2350	230	-	-	9	30
	80	80	95,5	2400	250	-	-	9	30
3 1/2	90	90	106	2750	280	-	-	9	30
4	102	102	118,5	3100	310	-	-	9	30

