

## VACUPRESS MARINE WASTE

Manguera de PVC blando de dos capas con espiral de acero galvanizado incorporada reforzada con fibra de poliéster, para aspiración e impulsión de líquidos. Para sistemas de descarga de aguas negras de embarcaciones.

|  |                                                                       |             |
|--|-----------------------------------------------------------------------|-------------|
|  | <b>SUPERFÍCIES LISAS</b><br>SMOOTH SURFACE                            | *****       |
|  | <b>FLEXIBILIDAD</b><br>FLEXIBILITY                                    | ****        |
|  | <b>RESISTENCIA A LA ABRASIÓN</b><br>ABRASION RESISTANCE               | **          |
|  | <b>TEMPERATURA DE USO</b><br>TEMPERATURE RANGE                        | -25°C +60°C |
|  | <b>RESISTENCIA QUÍMICA</b><br>CHEMICAL RESISTANCE                     | tabla PVC   |
|  | <b>RESISTENCIA AL APLASTAMIENTO</b><br>CRUSHING RESISTANCE            | ***         |
|  | <b>SISTEMA DE DESCARGA DE AGUAS NEGRAS</b><br>WASTE WATER TANK SYSTEM |             |

## 912916



Two-layer soft PVC hose with embedded galvanised steel spiral with polyester yarn reinforcement, for suction and delivery of liquids. For waste water systems of boats.

| Ø NOMINAL<br>Ø NOMINAL | Ø NOMINAL<br>Ø NOMINAL | Ø INTERIOR<br>Ø I.D. | Ø EXTERIOR<br>Ø O.D. | PESO<br>WEIGHT | RADIO CURVATURA<br>BENDING RADIUS | PRESIÓN TRABAJO<br>WORKING PRESS. | PRESIÓN ROTURA<br>BURSTING PRESS. | VACÍO<br>VACUUM    | LONGITUD ROLLO<br>COIL LENGTH |
|------------------------|------------------------|----------------------|----------------------|----------------|-----------------------------------|-----------------------------------|-----------------------------------|--------------------|-------------------------------|
| inch                   | mm                     | mm                   | mm                   | g/m            | mm                                | bar                               | bar                               | m H <sub>2</sub> O | m                             |
| 1                      | 25                     | 25                   | 36                   | 680            | 80                                | 16                                | 48                                | 9                  | 60                            |
| 1 1/2                  | 38                     | 38                   | 51                   | 1150           | 125                               | 14                                | 42                                | 9                  | 30                            |
|                        | 50                     | 50                   | 63,5                 | 1600           | 150                               | 12                                | 36                                | 9                  | 30                            |

