

VACUPRESS SUPER CHEMI

Manguera de caucho multicapa con espiral de acero galvanizado incorporada reforzada con fibra de poliéster, capa interior de poliolefina, para aspiración e impulsión de líquidos corrosivos.

912954



Multilayer rubber hose with embedded galvanised steel spiral with polyester yarn reinforcement, polyolefin underlayer, for suction and delivery of corrosive liquids.

	SUPERFÍCIES LISAS SMOOTH SURFACE	*****
	FLEXIBILIDAD FLEXIBILITY	**
	RESISTENCIA A LA ABRASIÓN ABRASION RESISTANCE	**
	TEMPERATURA DE USO TEMPERATURE RANGE	-25°C +80°C
	RESISTENCIA QUÍMICA CHEMICAL RESISTANCE	tabla LLDPE
	RESISTENCIA AL APLASTAMIENTO CRUSHING RESISTANCE	***

Ø NOMINAL Ø NOMINAL	Ø NOMINAL Ø NOMINAL	Ø INTERIOR Ø I.D.	Ø EXTERIOR Ø O.D.	PESO WEIGHT	RADIO CURVATURA BENDING RADIUS	PRESIÓN TRABAJO WORKING PRESS.	PRESIÓN ROTURA BURSTING PRESS.	VACÍO VACUUM	LONGITUD ROLLO COIL LENGTH
inch	mm	mm	mm	g/m	mm	bar	bar	m H ₂ O	m
3/4	19	19	27,5	340	100	25	80	9	60
1	25	25	33,5	430	120	25	77	9	60
	28,5	28,5	37,5	550	130	20	65	9	60
1 1/4	32	32	41	590	150	18	56	9	60
1 1/2	38	38	48,5	800	200	17	53	9	30
2	51	51	62,5	1150	250	14	42	9	30
2 1/2	63	63	74,5	1450	300	12	40	9	30

